



Features

- Down-leads axially and horizontally.
- Very low loss at high frequency, suitable for high current .
- High insulation resistance, long life due to self-healing effect.
- Widely used in high frequency, DC, AC and pulse circuits.

Configuration

Non-inductive, wound with metallized polypropylene films dielectric and electrode and copper-clad steel leads or flexible cord, outer wrapped of polyester and end sealed with epoxy resin



Specifications & Outline Drawing

Reference Standard	GB 10190-88(IEC 60384-16)	
Climatic Category	40/85/21	
Rated Voltage	160V, 250V, 400V, 630V, 1000V, 1200V	
Capacitance Range	0.010-30.0uF	
Capacitance Tolerance	±5%(J), ±10%(K), ±20%(M)	
Voltage Proof	1.6U _R (5s)	
Dissipation Factor	≤0.1%(20°C, 1KHz)	
Insulation Resistance	$\geq 25000M\Omega$ (CR≤0.33uF) $\geq 7500s$ (CR>0.33uF)	(20°C, 1min)

MPA

MPT

Dimensions

R.V. Size	250VDC		400VDC		630VDC	
	L	D	L	D	L	D
Cap.	Max	Max	Max	Max	Max	Max
0.010					14.0	7.0
0.015					14.0	7.0
0.022					14.0	8.0
0.033			14.0	8.0	19.0	8.0
0.047			14.0	8.0	19.0	9.0
0.068			19.0	8.0	19.0	11.0
0.10	14.0	8.0	19.0	9.0	27.0	11.0
0.15	19.0	8.0	19.0	10.0	27.0	13.0
0.22	19.0	9.0	27.0	10.0	33.0	13.0
0.33	19.0	11.0	27.0	12.0	33.0	16.0
0.47	25.0	11.0	27.0	13.0	33.0	18.0
0.68	25.0	13.0	33.0	15.0	33.0	20.0
1.0	25.0	13.0	33.0	17.0	38.0	21.0
1.5	33.0	15.0	33.0	21.0	44.0	22.0
2.2	33.0	17.0	38.0	22.0	44.0	27.0
3.3	33.0	19.0	44.0	26.0		
4.7	38.0	21.0				
6.8	44.0	23.0				
10.0	44.0	26.0				

R.V. Size	250VDC			400VDC			630VDC		
	W	H	T	W	H	T	W	H	T
Cap.	Max	Max	Max	Max	Max	Max	Max	Max	Max
0.010									
0.015							14.0	10.0	6.0
0.022							14.0	10.0	6.0
0.033							19.0	12.0	7.0
0.047				14.0	12.0	7.0	19.0	13.0	8.0
0.068				19.0	12.0	7.0	19.0	14.0	9.0
0.10	14.0	12.0	7.0	19.0	12.0	8.0	27.0	13.0	8.0
0.15	19.0	11.0	6.0	19.0	15.0	9.0	27.0	16.0	9.0
0.22	19.0	11.0	7.0	27.0	15.0	8.0	33.0	17.0	11.0
0.33	19.0	13.0	8.0	27.0	16.0	10.0	33.0	20.0	13.0
0.47	27.0	15.0	9.0	33.0	16.0	10.0	33.0	23.0	15.0
0.68	27.0	16.0	10.0	33.0	18.0	11.0	38.0	25.0	16.0
1.0	33.0	18.0	10.0	33.0	21.0	14.0	44.0	32.0	17.0
1.5	33.0	20.0	13.0	33.0	24.0	16.0	44.0	37.0	21.0
2.2	33.0	20.0	14.0	38.0	30.0	15.0	44.0	38.0	23.0
3.3	33.0	24.0	16.0	44.0	38.0	18.0			
4.7	38.0	25.0	16.0						
6.8	44.0	32.0	16.0						
10.0	44.0	38.0	18.0						