



Shenzhen Topmay Electronic Co., Ltd
深圳市亿普电子有限公司

Rm 3306, International Science and Technology Bldg, Central ShenNan Rd3007, FuTian,Shenzhen City,CN.
深圳市深南中路国际科技大厦 3306 室 TEL:0755-33341571/2,33340231,83279523;FAX: 0755-33341573

3mm Chip Metal Glaze Potentiometer

Scope

This specification applies to 3 mm Chip trimmer potentiometer with Metal - Glaze - Resistor, used in electronic equipment.

Feature

Plastic sealed shell, with good dust resistance.

Plastic sealed open structure, easy to install, easy to adjust. The installation foot and adjustment direction are optional.

It is suitable for all kinds of electronic products. There are many optional resistance values, The resistance value in the rated range can be adjusted arbitrarily, and can be applied to various circuits

Variety specifications, strong applicability, optional resistance value, resistance value can be arbitrarily adjusted within the rated range, can be applied to a variety of circuits.

Application

Glass glaze potentiometer is widely used in analog circuit regulation, sound equipment regulation, lighting equipment regulation and other fields.

It can realize the change of resistance value by rotating or sliding, to achieve the precise control and adjustment of the circuit signal.

Electric characteristics

Nominal Resistance	100Ω-1MΩ
Operating temperature	-40°C -- +100°C
Storage Temperature range	-10°C -- +40°C
Resistance Taper	B (Linear)
Resistance Tolerance	±25%
Rated Power	0.15W
Maximum operating Voltage	DC 50V
Rotational Angle	270°±20°
Rotational Torque	0.98-11. 76mN.m



Shenzhen Topmay Electronic Co., Ltd
深圳市亿普电子有限公司

Rm 3306, International Science and Technology Bldg, Central ShenNan Rd3007, FuTian,Shenzhen City,CN.
深圳市深南中路国际科技大厦 3306 室 TEL:0755-33341571/2,33340231,83279523;FAX: 0755-33341573

